


Product image	Description	ø	REF	Frequency of application ¹																			
	Gingiva cutter	ø 3.3 mm	382-333-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Gingiva cutter	ø 3.7 mm	382-337-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Gingiva cutter	ø 4.2 mm	382-342-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Gingiva cutter	ø 4.8 mm	382-348-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Gingiva cutter	ø 5.5 mm	382-355-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Depth drill	ø 2.0 mm	382-320-07	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Depth drill	ø 2.0 mm	382-320-09	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Depth drill	ø 2.0 mm	382-320-11	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Depth drill	ø 2.0 mm	382-320-13	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Depth drill	ø 2.0 mm	382-320-15	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 3.3 mm	382-333-09	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 3.3 mm	382-333-11	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 3.3 mm	382-333-13	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 3.3 mm	382-333-15	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 3.7 mm	382-337-07	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 3.7 mm	382-337-09	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 3.7 mm	382-337-11	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 3.7 mm	382-337-13	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 3.7 mm	382-337-15	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 4.2 mm	382-342-07	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 4.2 mm	382-342-09	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 4.2 mm	382-342-11	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 4.2 mm	382-342-13	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 4.2 mm	382-342-15	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20

¹ **Note:** With careful and correct maintenance, the drills and thread taps can be used for 15 – 20 applications thanks to the high-quality materials and workmanship (see also Surgery Manual pOstion for tioLogic® 989-999-20).

Further information is available at www.dentaurum.com.

² Use only for tioLogic® implants.

³ Use only for tioLogic® ST and tioLogic® TWINFIT implants.

Product image	Description	ø	REF	Frequency of application ¹																			
				1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 4.8 mm	382-348-07	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 4.8 mm	382-348-09	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 4.8 mm	382-348-11	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 4.8 mm	382-348-13	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 4.8 mm	382-348-15	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 5.5 mm	382-355-09	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 5.5 mm	382-355-11	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 5.5 mm	382-355-13	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Stepped countersink	ø 5.5 mm	382-355-15	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Expander	ø 3.3 mm	382-533-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Expander	ø 3.7 mm	382-537-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Expander	ø 4.2 mm	382-542-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Expander	ø 4.8 mm	382-548-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Expander	ø 5.5 mm	382-555-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Thread tap ² pOtion	ø 3.3 mm	382-833-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Thread tap ² pOtion	ø 3.7 mm	382-837-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Thread tap ² pOtion	ø 4.2 mm	382-842-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Thread tap ² pOtion	ø 4.8 mm	382-848-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Thread tap ² pOtion	ø 5.5 mm	382-855-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Thread tap ³	ø 3.3 mm	382-933-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Thread tap ³	ø 3.7 mm	382-937-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Thread tap ³	ø 4.2 mm	382-942-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Thread tap ³	ø 4.8 mm	382-948-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Thread tap ³	ø 5.5 mm	382-955-00	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20

¹ **Note:** With careful and correct maintenance, the drills and thread taps can be used for 15 – 20 applications thanks to the high-quality materials and workmanship (see also Surgery Manual pOtion for tioLogic® 989-999-20).

Further information is available at www.dentaurum.com.

² Use only for tioLogic® implants.

³ Use only for tioLogic® ST and tioLogic® TWINFIT implants.